

TITAN[®] COATINGS

VULCANTX155™ ELASTOMER MEMBRANE

COATING INCORPORATES ULTRA ADVANCED MIMETIC ELASTOMER COMPONENTS WHICH OFFER EXCEPTIONALLY DENSE YET FLEXIBLE MEMBRANE FORMING ABILITIES.

THIS DARK MATTER TECHNOLOGY® REINFORCED TOP COAT OFFERS OMNIPHOBIC PROPERTIES TO OUR PX10 BASE COAT AS WELL THE ABILITY TO SELF REGENERATE AND HEAL FROM ABRASIONS, SWIRLS AND LIGHT SCRATCHES.



PRECAUTIONS AND MAINTENANCE:

Never allow highly alkaline (ph12+) chemicals to sit or dwell on the surface for extended periods. Avoid washing/abrasion in the first 7 days. Maintain every 2-3 years with HYDROTX145™ and every 3-6 months with ULTRA.

Coating Type:

Top Coat

Durability:

Tested to: ASTM B117, ISO9227, ASTM D4587, ASTM D6577

Single layer: up to 5 years as top coat

Dual layer: up to 6 years as top coat

Dual Layers are recommended.

Stacking options:

PX10™ Base coat mandatory
HydroTx145™ may be applied on top of

Suitability:

Paint systems including gloss and matte
PPF Paint protection film- self healing.
PX10™ must be applied as base coat for new generation top coated films followed by VULCANTX155™
PPS Paint protection spray
Vinyl

Ultimate Durability Package

Base PX10™ - middle VULCANTX155™
- top - HYDROTX145™

TECHNICAL DATA:

Thickness: Max 5 m
Thermal Resistance: 600°C
Hardness: Max 10H
PH Tolerance: 1-13